



Circuits	A	B	C
2	2.0	8.0	4.6
3	4.0	10.0	6.6
4	6.0	12.0	8.6
5	8.0	14.0	10.6
6	10.0	16.0	12.6
7	12.0	18.0	14.6
8	14.0	20.0	16.6
9	16.0	22.0	18.6
10	18.0	24.0	20.6
11	20.0	26.0	22.6
12	22.0	28.0	24.6
13	24.0	30.0	26.6
14	26.0	32.0	28.6
15	28.0	34.0	30.6
16	30.0	36.0	32.6

### SPECIFICATIONS

Electrical

Voltage Rating: 100V AC, DC

Current Rating: 2A AC, DC

Withstand Voltage: 800V AC/ min.

Insulation Resistance: 1000MΩ/ min.

Temperature Range: - 25°C ~ + 85°C

Material

Wafer: High Temperature Plastic Nylon 46 UL94V-0

Pin: High Strength Brass With Tin Over Nickel Plated

Applicable PC Board Thickness: 0.8 ~ 1.6mm

Contact Resistance: Initial Value / 10MΩ max.

After environmental testing 20MΩ max.

( Unit: mm )

Unit	mm	Drawd By	Lin	Part No.	7002-Txx
Date	102/2/22	Checked By	Hsu	品 名	7002 SMT Top entry
Scale		Filename	7002SMT	客戶料號	

洋晟實業股份有限公司  
 ORECO ENTERPRISE CO., LTD.  
 TEL:02-27916536 FAX:02-27942101