



P.C.B. LAYOUT



**ELECTRICAL CHARACTERISTICS :**

CONTACT CURRENT RATING : 1AMPERES.

DIELECTRIC WITHSTANDING VOLTAGE : AC 500V R.M.S.

INSULATION RESISTANCE : 500 MEGOHMS MINIMUM AT DC 500V.

CONTACT RESISTANCE : 30 MILLIOHM MAXIMUM.

OPERATING TEMPERATURE : -55°C TO+105°C.

**MECHANICAL CHARACTERISTICS :**

CONTACT INSERTION FORCE : 3.7 KG MAXIMUM.

CONTACT SEPARATION FORCE : 1.2 KG MINIMUM.

**MATERIALS :**

CONTACT : PHOSPHOR BRONZE.

INSULATOR : P.B.T.U.L 94-V0 RATED/LCP

SHELL : BRASS.

**FINISHES :**

CONTACTS :GOLD FLASHED 1U",3U",5U",10U",15U",30U".

SHELL :NICKEL OR TIN .

單位 UNIT	mm	繪圖 DRAWN BY	Liu	PART NO.	Oreco Enterprise Co.,Ltd 洋晨實業股份有限公司 Tel: 886-2-27916536 Fax: 886-2-27942101	
日期 DATE	95, 10, 30	核對 CHECKED BY	Hsu			USB-A- 04PR
說明 DESCRIPTION		比例 SCALE				